

TEMADUR ELASTIC EXTRA

DESCRIPTION

A two component additive for polyurethane paints to improve the elasticity of the coat.

PRODUCT
FEATURES AND
RECOMMENDED
USES

- Is used in TEMADUR paints and varnishes in order to improve the elasticity and impact strength of the coat.
- Is recommended when flexible or brittle plastic materials are coated.
- Does not harm the weathering resistance of coating.

TECHNICAL DATA

Specific gravity 1.05 kg / I (mixed)

Mixing ratio and
product codeBase5 parts by volume990 1264445555677677777778777977797779777107

Recommended amount to be added

30 % by volume of a mixture of TEMADUR ELASTIC EXTRA and hardener to be added to to the TEMADUR mixture.

Directions for use Add the hardener separately to TEMADUR ELASTIC EXTRA and TEMADUR. Unite the mixtures and mix thoroughly, if necessary thin with thinner 1048.

N.B! Do not use TEMADUR ELASTIC EXTRA alone.

Colours TEMADUR ELASTIC EXTRA is colourless. It can be used untinted or tinted to

shades according to TEMADUR TCL base paint. If not tinted TEMADUR ELASTIC

EXTRA may impair the hiding power of the paint.

VOC The Volatile Organic Compounds amount to 450 ± 20 g/litre of paint.

HEALTH AND SAFETY Containers are provided with safety labels, which should be observed. Further

information about hazardous influences and protection are detailed in individual

health and safety data sheets.

A health and safety data sheet is available on request from Tikkurila Coatings Oy.

For professional use only.

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

tmk020802/990 7590